HellermannTyton

MCRFW-ENT



Article Number: 250-00017

InfoStream Multi-Channel Raceway Entrance End Fitting, HIPS, Office White, 1/pkg

RoHS

Base Data

Local Order Number	MCRFW-ENT
Туре	MCR-ENT
Color	Office White (OEWH)
Features and Benefits	 Raceway and fittings are manufactured from a UL 94V-0 rated material to insure compliance with codes All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standards Raceway and fittings are U.L. Listed to 600 Volts to meets new UL5A and CSA 22.2 No. 62-93 standards Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables
Product Description	The Multi-Channel Entrance End Fitting is used as a ceiling drop, conduit transition from end or base, or low voltage entrance from end or base of raceway. Knockouts are provided for dual .75", 1", 1.25", 1.75", 2" and 2.5" connections.
Short Description	InfoStream Multi-Channel Raceway Entrance End Fitting, HIPS, Office White, 1/pkg

Product Dimensions

Logistics and Packaging

Quantity per	bag
Package Quantity (imperial)	1
Package Quantity	1

Material and Specifications

Material	Polystyrene, high impact resistant (PS-HIR)
Material Shortcut	HIPS
ROHS Conformity	Yes

© HellermannTyton 2014