

Specification Sheet

Part Number: MCRFW-PTF



Raceway and fittings are manufactured from a UL94 V0 rated material to ensure compliance with codes.

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard.

Raceway and fittings are UL Listed to 600 Volts to meet new UL5A and CSA 22.2 No. 62-93 standards.

InfoStream Multi-Channel Raceway Power Transition Fitting, PVC, Office White, 1/pkg

Article Number	250-00024
Type	MCR-PTF
Color	Office White (OEWH)
Quantity Per	bag
Product Description	Knockouts are provided for TSRP1, TSRP2 and TSRP3 surface raceway.
Short Description	InfoStream Multi-Channel Raceway Power Transition Fitting, PVC, Office White, 1/pkg
Global Part Name	MCR-PTF-PVC-WH

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V-0
Halogen Free	No
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
UL Listed (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	3925900000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HellermannTyton:](#)

[MCRFW-PTF](#)